



Product data sheet

hz acoustic plaster 03

Area to use:

Acoustic plaster for hz panels 005, 007, 009, 011, 015 016 and on acoustic fleece on perforated plasterboard. Can be used in wet areas.

Foundation:

Ready to use, fiber based acoustic plaster for interior use.

Color:

Standard very white, and can be tinted in most NCS and RAL colors.

Packing size:

15 kg bucked.

Application rate:

Approx. 4 to 5 kg per sq. m depending on system.

MAL-code (1993):

00 - 1

VOC content:

EU-VOC threshold: category A/a/wb 30 g/l (2010) This product contains a maximum of 0 g/l VOC.

Fire class:

Euro class A2-s1, d0 by finish system on hz acoustic plate 005, 007, 009 and 011
Euro class B-s1, d0 by finish system on hz acoustic panel 015 and 016

Health and safety:

EUH208 - Contains 1,2-benzisothiazol-3(2H)-one, May produce an allergic reaction.
EUH210 - Safety data sheet available on request.

Storage:

Keep container closed tightly, protect against frost, do not store at temperatures above + 30°C and protect from direct sunlight. Storage capability of original container: 12 months.

References:

For further information of safety for transport, storage, handling and disposal, please read safety data sheet. The above mention information describes the actual stat of our technical knowledge and our experience. They do not exempt the user from carrying out their own test due to the many influences during the application process and while working with our products. A legally binding assurance of certain attributes, nor suitability for a specific application purpose cannot be deduced from the description provided above. Any licenses as well as rules and regulations are to be observe by the recipient and are their responsibility. We reserve the rights to undertake technical modification to our product as well as to packaging. Because of different materials, surfaces and deviating working conditions, there can be no general guarantee of the outcome or adhesion.

version 2.18/hh