

Product data sheet

hz glue S1



Area to use:

hz glue is used for gluing hz acoustic sheet 015 and 016 on interior surfaces such as plasterboard, concrete and previously painted surfaces.

Foundation:

Polyvinyl acetate dispersion adhesive, PVA

Color:

Clear, non

Packing size:

10 Liter

Application rate:

0.600 – 0.800 liter pro sq. meter

Fire class:

Non combustible

Storage:

Keep container closed tightly, protect against frost, do not store at temperatures above + 30°C and protect from direct sunlight.

Processing / handling:

The substrate must be clean, dry and free from dust and grease. The substrate must be primed with hz isoground before startup. Ensure good coverage of unlatched areas
Adhesives are applied with lamb wool roll, or hz sprayer in a smooth layer on the surface, and the acoustic plate is applied to the wet mass. Make sure the plates are pressed well into the wet adhesive to prevent air bubbles. Read supplier instructions

Processing time (opening time):

Glue is open 5-9 min.

Hardened after 24 hours with 20 degrees and max 65% RF.

Condition on site:

Keep temperature at minimum 20 degrees and maximum 30 degrees when processing and during drying time at maximum 60% relative humidity. Use ventilation ore dehumidifier for drying.

Cleaning tools:

Clean immediately in warm water after use. Dried glue can only be removed mechanically or by use of acetone ore like other solvents

References:

For further information of safety for transport, storage, handling and disposal, please read safety data sheet. The above mention information describes the actual stat of our technical knowledge and our experience. They do not exempt the user from carrying out their own test due to the many influences during the application process and while working with our products. A legally binding assurance of certain attributes, nor suitability for a specific application purpose cannot be deduced from the description provided above. Any licenses as well as rules and regulations are to be observe by the recipient and are their responsibility. We reserve the rights to undertake technical modification to our product as well as to packaging. Because of different materials, surfaces and deviating working conditions, there can be no general guarantee of the outcome or adhesion.

Version 2.18/hh

